RECEIVED CENTRAL FAX CENTER

10/774,389

DOCKET NO. PTGF-03083

2

APR 1 8 2007

## **AMENDMENTS TO THE CLAIMS:**

Claim 1. (Currently amended) A light emitting apparatus, comprising:

a semiconductor light emitting element including a substrate, wherein light radiates from a light emission surface of the substrate of said light emitting element, the light emission surface being provided on the substrate opposite to an electrode forming surface of the substrate; and

a transparent structure mounted on the light emission surface of the substrate, wherein the transparent structure is optically connected with the light emission surface and has a light distribution characteristic based on a three-dimensional shape of the transparent structure,

wherein the transparent structure comprises comprises a side surface through which to allow the light to be discharged from the transparent structure.

- Claim 2. (Canceled).
- Claim 3. (Original) The light emitting apparatus according to claim 1, wherein: the transparent structure has a thickness of half that of the semiconductor light emitting element to twice the length of a shorter side of the semiconductor light emitting element.
- Claim 4. (Original) The light emitting apparatus according to claim 1, wherein: the transparent structure has a microscopic uneven surface to diffuse light.
- Claim 5. (Original) The light emitting apparatus according to claim 1, wherein: the transparent structure has a reflection layer formed on its surface.
- Claim 6. (Previously presented) The light emitting apparatus according to claim 17, wherein:

one of the lead frames has a cup portion, and

the transparent structure is fixed on the cup portion through adhesive resin with light diffusion material mixed therein.

10/774,389

DOCKET NO. PTGF-03083

3

Claim 7. (Previously presented) The light emitting apparatus according to claim 17, wherein:

the electrodes do not transmit light.

Claim 8. (Previously presented) A light emitting apparatus, comprising:

a semiconductor light emitting element that includes a substrate and that radiates light from a light emission surface provided on the substrate of the semiconductor light emitting element opposite an electrode forming surface of the substrate;

lead frames that are electrically connected to electrodes formed on the electrode forming surface through wires;

a transparent structure that is mounted on the light emission surface of the substrate and optically connected with the light emission surface and has a light distribution characteristic based on a three-dimensional shape of the transparent structure; and

light transmitting resin that seals the semiconductor light emitting element and the transparent structure, the light transmitting resin including a phosphor to wavelength-convert light emitted from the semiconductor light emitting element,

wherein the transparent structure comprises a side surface through which to allow the light to be discharged from the transparent structure.

- Claim 9. (Original) The light emitting apparatus according to claim 8, wherein: the light transmitting resin contains two or more kinds of phosphors.
- Claim 10. (Previously presented) The light emitting apparatus according to claim 1, wherein the semiconductor light emitting element comprises the substrate, a buffer layer, an n-type semiconductor layer, a light-emitting layer, and a p-type semiconductor layer.
- Claim 11. (Previously presented) The light emitting apparatus according to claim 1, wherein the semiconductor light emitting element comprises a gallium nitride system compound semiconductor.
- Claim 12. (Previously presented) The light emitting apparatus according to claim 1.

10/774,389 DOCKET NO. PTGF-03083 4

wherein the transparent structure comprises a light transmitting material comprising at least one of SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub>, SiC, Si<sub>3</sub>N<sub>4</sub>, AlN, ZrO<sub>2</sub>, borosilicate glass, and alumino-silicate glass.

- Claim 13. (Previously presented) The light emitting apparatus according to claim 1, wherein the substrate comprises sapphire.
- Claim 14. (Previously presented) The light emitting apparatus according to claim 1, wherein the transparent structure is bonded to the substrate by an adhesive layer.
- Claim 15. (Previously presented) The light emitting apparatus according to claim 14, wherein the adhesive layer comprises a transparent adhesive.
- Claim 16. (Previously presented) A light emitting apparatus, comprising:

a semiconductor light emitting element that includes a substrate and that radiates light from a light emission surface provided on the substrate of the semiconductor light emitting element opposite to an electrode forming surface of the substrate;

lead frames that are electrically connected to electrodes formed on the electrode forming surface through wires;

a transparent structure that is mounted on the light emission surface of the substrate and optically connected with the light emission surface and has a light distribution characteristic based on a three-dimensional shape of the transparent structure; <u>and</u>

light transmitting resin that seals the semiconductor light emitting element and the transparent structure,

wherein the transparent structure comprises a side surface through which to allow the light to be discharged from the transparent structure.

- Claim 17. (Previously presented) The light emitting apparatus according to claim 1, further comprising lead frames that are electrically connected to electrodes formed on the electrode forming surface through wires.
- Claim 18. (Previously presented) The light emitting apparatus according to claim 1,

10/774,389 DOCKET NO. PTGF-03083

5

further comprising light transmitting resin that seals the semiconductor light emitting element and the transparent structure.

- Claim 19. (Previously presented) The light emitting apparatus according to claim 8, wherein the transparent structure is mounted on the light emission surface of the substrate by an adhesive layer.
- Claim 20. (Previously presented) The light emitting apparatus according to claim 16, wherein the transparent structure is mounted on the light emission surface of the substrate by an adhesive layer.
- Claim 21. (Previously presented) The light emitting apparatus according to claim 1, wherein the side surface comprises an inclined plane.
- Claim 22. (Previously presented) The light emitting apparatus according to claim 8, wherein the side surface comprises an inclined plane.
- Claim 23. (Previously presented) The light emitting apparatus according to claim 16, wherein the side surface comprises an inclined plane.